FENCE-PRO Mule



FENCE-PRO Mule

Standard Features

- 4m mast (extra heavy duty)
- 4 Bank Valve (1 spare function)
- Hydraulic top link
- Hydraulic side tilt
- 230 kg block
- Height adjustable feet
- 60mm diameter mast pivot
- External pressure relief valve

Options

- 250kg or 270 kg block upgrade
- 420mm or 900mm side mount unit
- 250mm mast shift
- 4.5m hydraulic hinge mast
- Rock Spike Extractor system (RSE)
- Hyd auger to fit rock spike unit
- Hyd auger system without RSE
- Ultra/Mule hydraulic post lifter
- Sidemount unit leg roller

Note the Mule shown is fitted with various options for display purposes.



The Rock Spike Extractor System (RSE), can be used with a spike, an auger, or both.



The auger swings back into the transport position so you can drive the post into the hole.

The **Mule** is an extremely robust and versatile driver capable of very high workloads in difficult conditions. The mast is the same construction as the Ultra G2 and can be fitted with a wide range of options so as to adapt to all types of terrain and soil types.

The **Mule** can mount directly behind the tractor, or on a sidemount or a rearshift unit. One man post positioning is easy with the mast shift and sidemount combo . Sandblasted and painted with an industry leading system ensures long life and durability. Please contact the Fence-Pro team for more information.

MAXAM Machinery PO Box 4114 422 Railway Rd Palmerston North 4442 0800 362 776 info@fence-pro.co.nz www.fence-pro.co.nz



This photo above shows the RSE with the spike in the transport position and ready to be pulled out in the photo below.



