

NK Proven design and quality

400 / 600 / 800



Proven design and quality
NK

400 / 600 / 800

Well proven sprayers

The HARDI NK sprayer is one of the most versatile sprayers ever built. The NK is used by professional plant growers all over the world. It finds its use in traditional farming, horticulture, orchards, vineyards and on grasslands.

The NK is a durable and well proven sprayer that offers far more features and options than you would expect from a sprayer in this class.

Chassis

The chassis is the base of a long lasting sprayer. The design of the NK chassis provides for a centre of gravity that is both low and close to the tractor. The design furthermore offers easy service accessibility. The NK chassis is zinc-phosphate treated before being coated with polyester powder. This ensures outstanding weather and chemical resistance on all chassis parts.

Booms

All booms for the NK

... are, like the frame, zinc-phosphate treated before being coated with polyester powder. This with a proven design ensures long and reliable use of the boom.

SB boom

The 6, 8 and 10 m SB booms are directly mounted to the frame. A mechanical and hydraulic boom lift makes the height adjustment easy and safe. If the NK sprayer will be used in crops with are higher than 50 cm a lift must be ordered to fulfill the EU regulations.

MB boom

The 12 m MB boom features a trapeze suspension for self-stabilisation and prolonged boom life. On the SB booms they trapeze suspension is an optional.

SB boom



MB boom



Break-away

All booms have an adjustable spring loaded break-away to protect the boom in case of accidental encounter with an obstacle in the field.



No dripping from nozzles

The single SNAP-FIT nozzle holders have a built-in non-drip diaphragm check valve. The non-drip valve ensures no dripping from the nozzles when the main on/off is closed. The SNAP-FIT system furthermore ensures that all nozzles are in the correct position.

A large range of high quality HARDI nozzles is available to suit any spray task.




Technical specifications

Tank size, l	Boom model	Width	Pump model	Pump capacity, l/min	Size, L x W x H	Weight, kg
400	SB	6 m	603 / 1203 / 1303	42 / 99 / 114	140 x 190 x 170	150
	SB	8 m	603 / 1203 / 1303	42 / 99 / 114	140 x 190 x 210	160
	SB	10 m	603 / 1203 / 1303	42 / 99 / 114	140 x 190 x 210	180
600	SB	6 m	603 / 1203 / 1303	42 / 99 / 114	140 x 190 x 170	170
	SB	8 m	603 / 1203 / 1303	42 / 99 / 114	140 x 190 x 210	180
	SB	10 m	603 / 1203 / 1303	42 / 99 / 114	140 x 190 x 210	200
	MB	12 m	603 / 1203 / 1303	42 / 99 / 114	140 x 190 x 220	240
800	SB	6 m	1203 / 1303	99 / 114	140 x 190 x 170	200
	SB	8 m	1203 / 1303	99 / 114	140 x 190 x 210	210
	SB	10 m	1203 / 1303	99 / 114	140 x 190 x 210	230
	MB	12 m	1203 / 1303	99 / 114	150 x 190 x 220	270

Optionals




15 l CleanWater tank




25 l ChemFiller




60 l RinseTank




Hydraulic boom lift



TRIPLET



Foot step



Remote control




Manual boom lift



Tank

The high-impact polyethylene tank has a deep sump that ensures complete emptying of the tank. The tank design maximises liquid agitation as well as ensuring easy and efficient tank cleaning with the use of a tank cleaning nozzle. The top mounted suction filter on the 400, 600 and 800 l tanks makes it safe and easy for the operator to perform routine maintenance of the filter screen.

The NK sprayer comes standard with pressurised agitation, that ensures consistent agitation of even the most difficult mixtures.



Pump

HARDI pumps are designed for the application of chemicals and liquid fertiliser. The diaphragms separate the liquid from the vital parts of the pump such as its bearings and crankshaft, ensuring reliable and durable operation.

HARDI diaphragm pump features:

- Self-priming
- Able to run dry without damage
- Easy to service without special tools
- Grease lubricated crankcase
- Chemical resistant diaphragms and valves



Control

The NK line offers as standard the unique and reliable HARDI BK-180 control unit. This control unit comes with a long list of standard features.

- Main on/off that diverts all liquid back into the tank
- Safety valve
- Pressure filter
- Pressure gauge
- Valve for pressure agitation
- Minimum of 3 distribution valves with constant pressure system
- HARDI-MATIC for constant application rate regardless of RPM variations
- All these features ensure accurate and reliable application of all plant protection chemicals.

SPECIFICATIONS

- **Tank:** 400, 600 and 800 l high impact polyethylene
- **Frame:** Low centre of gravity close to tractor
- **Diaphragm pump:** Reliable, high capacity and easy to service
- **Operating unit:** Manual operated HARDI BK-180
- **Booms:** Manual folded 6, 8 and 10 m SB boom
Manual folded 12 m MB boom

- Versatile
- Durable
- Simple operation
- Easy to service



Nørre Alslev,
Denmark



Lleida,
Spain



Savigny,
France



Beaurainville,
France



Davenport,
USA



Adelaide,
Australia

HARDI

The Sprayer

HARDI INTERNATIONAL A/S

is an international group whose basic idea is to satisfy the user's requirements for quality products which ensure efficient, punctual and precise application of crop protection products. Our world-wide distribution and sales network comprise more than 100 countries where we are represented by importers, agents and sales subsidiaries. These are situated in Sweden, Norway, Denmark, the UK, France, Spain, North America, Germany and Australia.

Since 1957 HARDI has committed to the ever-increasing demands for efficient and precise plant protection. HARDI is the trendsetter within application of crop protection products. To achieve this position continued developments and innovation are essential. HARDI is committed to the long term future of plant protection.

Testing procedures

Sprayers leaving HARDI INTERNATIONAL A/S are tested according to the strictest quality standards.

The staff of the assembly line is accredited to match the demands of the Danish testing scheme, the UK NSTS (National Sprayer Testing Scheme), and the German JKI (Julius Kühn Institut). This ensures that the highest quality sprayers are delivered to farmers.



Superb surface treatment

The high-technology surface treatment contains 13 treatments, including a pre-treatment and powder coat painting of all major components.

Together with the Delta/Magni treatment of nuts, bolts and other items, we supply high corrosion protection of our products.



HARDI INTERNATIONAL A/S

Herthadalsvej 10 · 4840 Nørre Alslev · Tlf.: +45 43 58 85 00 · Fax: +45 43 58 85 20
E-mail: hardi@hardi-international.com · www.hardi-international.com



#HARDIsprayers