

Kubota



KUBOTA DIESEL TRACTOR

B

B3000HSDCC New Factory Cab Tractor

Kubota's versatile new B3000 Factory Cab Tractor delivers the perfect blend of power and performance to take on any task.



*This information is sourced from overseas and may not necessarily apply locally. It is essential that you confirm specifications and other information with your local Kubota dealer.

Kubota's all-weather B3000HS power, and versatility to take

Kubota's new B3000HSDCC Factory Cab Tractor strikes an ideal balance between power and versatility. Boasting a spacious air-conditioned cab, a powerful 30HP engine, 23 PTO HP, and a smooth 3-range HST, it is tough enough to take on heavy-duty jobs, and small enough to manage more precise tasks in comfort regardless of the season or weather. For improved operation, the B3000 cab tractors feature an easy-to-read dash panel, mid PTO, tilt-steering and much more to get the job done.

Diesel Engine

The B3000 cab model tractor features a smooth-running 30HP, 4-cylinder, liquid-cooled diesel engine, with Kubota's E-TVCS (three-vortex combustion system) for increased power and high torque.



Mechanical cruise control

To keep your working speed constant, simply set the infinite mechanical cruise control lever to your desired speed—and go.

Hydraulic Control Systems

B3000HSDCC's position control valve gives you more precise 3-point hitch control of your rear implements when attaching/detaching implements or when performing sensitive jobs.



**DCC tractor has the size,
on jobs of all sizes.**



Comfortable factory cab

The B3000 cab model's powerful heater and air conditioner combined with increased insulation from outside elements ensure you'll complete your work in comfort year around.

Cab Standards:

- Rear wiper
- Armrest
- Front work light
- Rear defogger with 60A alternator

Cab options:

- Halogen rear work lights
- Radio/CD or radio
- Radio mounting kit
(Speaker included)

KUBOTA DIESEL TRACTOR
B3000HSDCC

Specifications

Model			B3000HSDCC
Engine			
Type			E-TVCS, liquid cooled, 4-cylinder diesel
Make, Model			Kubota V1505-E3-D21-Q2
PTO horsepower	HP (kW)		23.0 (17.1)
Engine gross horsepower	HP (kW)		30.0 (22.3)
Rated RPM	rpm		2600
Bore and stroke	mm		78 x 78.4
Displacement	cc		1498
Air cleaner			Dual paper element
Lubrication			Forced lubrication
Cooling system			Pressurized radiator
Radiator fan			Radial air flow
Capacities			
Fuel tank	ℓ		31.0
Cooling system	ℓ		5.2
Engine oil	ℓ		4.1
Transmission case	ℓ		15.0
Drive train			
Clutch			N / A
Transmission			HST (3 ranges)
Differential lock			Standard
Final drive			Spur gear
Brake			Multi-plate wet disc
PTO			
Type			Independent
Rear	rpm		540
Mid	rpm		2500
Hydraulics			
Type			Open center
Pump			Dual pump
Total pump output	ℓ/min.		34.5
Hydraulic outlet			Front outlet, Rear outlet
3-point hitch			Category I
Hydraulic control system			Position control valve
Lift capacity	at lift point	kg	970
	24" behind LP	kg	760
Steering			Hydraulic power steering
Standard tyre size			
Front (Farm)			7-12
Rear (Farm)			12.4-16
Traveling speeds (at rated engine rpm)			
Forward	km/h		0-19.5
Reverse	km/h		0-15.5
Dimensions			
Overall length (w/o 3P)	mm		2640
Overall width (min. tread)	mm		1365
Overall height	mm		2150
Wheelbase	mm		1666
Ground clearance	mm		370
Turning radius with brake	m		2.1
Weight	kg		1030
Other Features			
Arm Rest			Std.
Front Work Light			Std.
3pt-hitch Lower Link			Telescopic
3pt-hitch Lower Link stabilizer			Telescopic
3pt-hitch Lift Rod (Right)			Ratchet Type

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.

©2011 Kubota Corporation



KUBOTA Tractor Australia Pty Ltd

25-29 Permas Way, TRUGANINA Vic, 3029
 Freecall: 1800 334 653
 Email: sales@kubota.com.au

Web Site: <http://www.kubota.com.au>

CB Norwood Distributors Ltd

PO Box 1265, 888 Tremaine Avenue,
 Palmerston North 0800 KUBOTA
 Tel: 06 356 4920 Fax: 06 356 4939

Web Site: <http://www.kubota.co.nz>