





Contour Following System






■ Barrel type rotors + crop seal



■ Rotor seal system





Fully sealed drive area



3300IV

WYXXXX 3300IV



The spring loaded breakaway linkage is stronger and suits Category 3 tractor quick hitch systems. MAXAM 3300 mowers are extremely quick to hook on and use anytime.



MAXAM 3300 rotors now share the same robust construction as the 2500. Optional topping skids clip under the skid and locate with the bolt hole shown.



The chassis is sand blasted and then coated with a high quality two pack paint system for long term durability. MAXAM mowers are designed to withstand the rigours of farm mowing.

MAXAM 3300IV Multipurpose mowers are ideal for all farm mowing and topping. They are easy and safe to operate, and the full spread of grass from the Wilter spreaders ensures the 3300IV is the ultimate farmers mower.

Precutting for cows

The 3300IV suits dairy farmers as they can pre cut the grass into rows before feeding the strip to the cows. This wilts the grass, raising the sugar content (energy) and minimising the risk of bloat.

Topping after the cows

Generally farmers spread the toppings when topping after the cows have grazed, to spread the dung and to ensure a quick even regrowth.

Multipurpose mower

The 3300IV is a genuine multipurpose mower as it can be used for mowing silage, baleage, and hay, as well as topping to control nuisance growths. The 3300IV is simple to set up and use, and gives excellent results every time.

3300IV Technical Specifications

Cutting Width 3.3m (10′ 10″)

Overall Transport 3.18m (10′ 5″)

Height adjustment 25mm - 75mm

PTO Speed 1000 rpm

Tractor size 90+ HP

Weight 650kg

Red, Blue, Straight

Note
Optional topping skids

to get 75mm topping

height

MAXAM Machinery

422 Railway Rd Palmerston North New Zealand

Email info@maxam.net.nz Web www.maxam.net.nz FREEPHONE 0800 108 563

