

PERFORMANCE WITH **ENDURANCE**



▲ PERFORMANCE WITH ENDURANCE



NEW and EXCITING, yet drawing from generations of both engineering innovation and in-field practical development.

The **GLABER** range of mowers combines state-of-art computer aided design, modern processes and materials, with time and field proven best technologies.

The two prime qualities of the new **GLABER** mowers are

- Ultimate grass cutting performance
- Machine endurance

The fact that the new mowers are also sleek and stylish is merely a by-product of good design!

Save money by dealing direct with the Manufacturer

www.glaber.co.nz



UPPERCUT 2700

Glaber is pleased to introduce the new UPPERCUT 2700, if you need to cut grass, we need to talk!

We have designed this mower to meet the needs of the New Zealand farmer better than any other mower. The machine embodies time and field proven technologies with the most modern production methods, delivering a high performing and great value package.

The UPPERCUT 2700 has a cutting width of 2.7 metres, is engineered to cut grass superbly, and can be used for either “Topping” or Hay Mowing. And every component is built tough and amazingly strong to provide years of reliable service.



SPECIFICATIONS

Cutting Height	170mm - 0.0mm Adjusts in 10mm Increments	
Cutting Width	2695.4mm	
Total Width	2940mm	
Length at longest point	1435mm	
Weight	588kg	
Rotors/Blades	3/9	
Offset Option	440mm	
Slasher Bar Option	With Flails for rough ground	
	540 PTO Gearbox	1000 PTO Gearbox
Blade Tip Speed (metres/second)	80	77
Gearbox Strength	65HP	122HP

FEATURES

1	Rotationally moulded guards won't rust, scratch or dent	2	Big SKF sealed bearings
3	5mm thick plate deck, and rugged heavy frame built to last	4	Oversize spindles (40mm diameter)
5	Heavy duty Italian gearbox 540rpm rated 65Hp, 1000 rpm rated 122 Hp	6	Automatic belt tensioners maintain correct belt tension for long life and effective power transmission
7	Twin vee belt drive out to left and right hand spindles, smooth power transmission, very long lasting and cheap to replace.	8	Rugged skids, wear resistant steel, large flat running surface with all edges upturned for smooth cornering without “digging in”, simple height adjustment.
9	Entire frame Sandblasted/Zinc sprayed/ two coat paint system, unsurpassed metal protection	10	Heavy cutter disk, triangular shape with three European made cutter tips, nine cutting tips over 2.7 metres gives high performance fine cutting
11	Easy to maintain, only three grease nipples easy to access (not under cover)	12	Turbo vanes capture the airflow and distribute the cut grass out the back of the mower evenly across the cutting path
















GREEN KEEPER 2700

Built with professional lawn care in mind, the Green Keeper 2700 is the ultimate tow behind mowing solution.

Made to be fitted to the 3 point linkage of a tractor. With a cutting width of 2.7 metres the stylish and rugged Green Keeper 2700 is ideally suited for use in public spaces such as parks, school fields and golf courses, and would also be suitable for other environments such as airfields.



FEATURES

	Rotationally moulded guards won't rust, scratch or dent		Big SKF sealed bearings
	5mm thick plate deck, and rugged heavy frame built to last		Oversize spindles (40mm diameter)
	Heavy duty Italian gearbox 540rpm rated 65Hp, 1000 rpm rated 122 Hp		Automatic belt tensioners maintain correct belt tension for long life and effective power transmission
	Twin vee belt drive out to left and right hand spindles, smooth power transmission, very long lasting and cheap to replace		Full width front roller 170mm diameter with 7mm thick wall, rugged, runs smoothly, ground levelling effect. Easy to adjust height by turnbuckle
	Entire frame Sandblasted/Zinc sprayed/ two coat paint system, unsurpassed metal protection		Easy to maintain, only three grease nipples easy to access (not under cover)
	Short rollers on trailing edge to help avoid grass scalping, easily height adjustable		Heavy cutter disk, triangular shape with three European made cutter tips, nine cutting tips over 2.7 metres gives high performance fine cutting
	Turbo vanes capture the airflow and distribute the cut grass out the back of the mower evenly across the cutting path		

SPECIFICATIONS

Cutting Height	125mm - 0.0mm Rear roller Adjusts in 12.5mm Increments	
Cutting Width	2695.4mm	
Total Width	2800mm	
Length at longest point	1500mm	
Weight	711kg	
Rotors/Blades	3/9	
	540 PTO Gearbox	1000 PTO Gearbox
Blade Tip Speed (metres/second)	80	77
Gearbox Strength	65HP	122HP



Factory 31 Johnston Way / Whakatu / Hastings

Postal 1019 Omaha Road / Hastings
New Zealand

Phone: 06 8766337

sales@glaber.co.nz

www.glaber.co.nz